

LCD MONITOR

LM-20XI



16:9



HD+

LED

Model	LM-20XI
LCD Size	19.5" Wide TFT Active Matrix LCD Display
Light source	LED backlight
Active area	432.0(H) x 239.76(V)
Aspect Ratio	16 : 9
Brightenss (Typ.)	250 cd/m ²
Contract Ratio (Typ.)	1000 : 1
View angle	170(H) / 160(V)
Response time	5 ms
Viewable size	435.3(H) x 243.06(V)
Pixel Pitch	0.27(H) / 0.27(V) mm
Display Color	16.7M
Maximum Resolution (pixels)	1600 x 900@60Hz
Hor.Frequency (KHz)	30-80KHZ
Ver.Frequency (KHz)	60-75HZ
Input Connector	D-sub / DVI / Audio in / Power in
OSD	Multi-Language
Power consumption	20W
Power Type	AC100-240V - 1.1A
Speaker	1W x 2 (2W x 2 Optional)
Dimension	520 x 105 x 390mm
Container Loading	20 ft / 1250 pcs

Features

Energy Efficient

The led backlighting technology, uses up to 33% less energy than previous equivalent-sized LCD monitors. Not only saving energy but also prolonging the monitor life.



Front View



Side View



Back View

