

Power Supply

SFX 12V 3.21 Version PN Series-180/230/250



Features

- 5 outputs (-12V, +5V, +3.3V, +12V, 5VSB)
- Low acoustic noise
- High reliability
- Remote On / Off
- Built-in EMI filter
- Thermal fan speed control (Optional) (SFX 2.3/3.1)
- Active PFC function (Optional) (SFX 2.3/3.1)

Environment

Operation Temp.	10°C ~ 50°C
Storage Temp.	-20°C ~ +60°C
Storage altitude	sea level to 50000ft
Operating & Storage humidity	10% ~ 95%RH
Operating altitude	sea level to 10000ft

Specification

Efficiency	> 65% (max.load)
Hold Time	> 17ms (max.load)
Rise Time	< 20ms (max.load)
Short Protection	All outputs
Overvoltage Protection	+5V, +12V, +3.3V

Input

Voltage Range	90~135 / 180~264VAC (slide switch)
Frequency Range	47~63 Hz

Mechanical

Dimension : 125(W) x 77(H) x 100(D) mm

Cables

180W~250W	x1	x1	x2	x2

Model	180 (SFX 3.21)	230 (SFX 3.21)	250 (SFX 3.21)
AC Input	115V 60Hz 230V 50Hz	4A 2A	6A 3A
+5V	14A	15A	15A
+3.3V	13A	14A	16A
+12V	10A	15A	16A
+12V1	-	-	-
+12V2	-	-	-
-12V	0.3A	0.3A	0.3A
+5Vsb	2A	2A	2A
+3.3V & 5V MAX	80W	85W	90W
Max Power	180W	230W	250W

- Regulation tolerance shall include temperature change, warm up drift and dynamic load.
- Ripple and noise are measured differentially at the supply using load that are each shunted by at least a 0.1uf ceramic disc capacitor and a 10uf electrolytic capacitor bandwidth up to 20 MHz.