

Power Supply

TFX 12V 2.01 Version PJ Series-180/230/250



Features	Environment	
----------	-------------	--

- 5 outputs (-12V, +5V, +3.3V, +12V, 5VSB)
- Low acoustic noise
- High reliability
- Remote On / Off
- Built-in EMI filter
- Thermal fan speed control

Operation Temp.	10°C ~ 50°C
Storage Temp.	-20°C ~ +60°C
Storage altitude	sea level to 50000ft
Operating & Storage humidity	10% ~ 95%RH
Operating altitude	sea level to 10000ft

Specification	Input	
---------------	-------	--

Efficiency	> 65% (max. load)
Hold Time	> 17ms (max. load)
Rise Time	< 20ms (max. load)
Short Protection	All outputs
Oversvoltage Protection	+5V, +12V, +3.3V

Voltage Range	90 ~ 135 / 180 ~ 264VAC (slide switch)
Frequency Range	47 ~ 63 Hz

Mechanical

Dimension : 65(W) x 85(H) x 175(D) mm

Cables



20+4 Pin




P4 Connector (CPU)



4 Pin Connector (IDE)



SATA Connector



4 Pin Connector (Floppy)

150W-250W	x1	x1	x2	x2	-
------------------	----	----	----	----	---

Model	180	230	250	
AC	115V 60Hz	4A	6A	7A
Input	230V 50Hz	2A	3A	4A
	+5V	14A	15A	15A
	+3.3V	13A	14A	16A
DC	+12V	10A	15A	16A
Output	-12V	0.3A	0.3A	0.3A
	+5Vsb	2A	2A	2A
+3.3V & 5V MAX	80W	85W	90W	
Max Power	180W	230W	250W	

- Regulation tolerance shall include temperature change, warm up drift and dynamic load.
- Ripple and noise are measured differentially at the supply using load that are each shunted by at least a 0.1uf ceramic disc capacitor and a 10uf electrolytic capacitor bandwidth up to 20 MHz.